

CONO cubo

NewTec
Design : Audio



CONO cubo

Straight Design for ceiling mounting installation.

The CONO cubo can be fixed directly to the ceiling and offers a discreet look in high quality anodised aluminium (CONO cubo S) and in carbon-fibre-reinforced plastic (CONO cubo M). Its small size of 105 mm x 105 mm (CONO cubo S) and 110 mm x 110 mm (CONO cubo M) makes it a little but powerful station, which complements the ceiling with its own particular design, especially on ceilings with exposed concrete. The CONO cubo can also be installed on the wall. We recommend an installation height of at least 2 meters.

Technical Data

CONO cubo S

Type	Wall / Ceiling mountable speaker
Principle	One way speaker
Dimensions W x L X H	105 x 105 x 105 mm
Weight	2 kg
Enclosure	Aluminium
Colours	Silver, white - all RAL colors available on request
Equipment	1 NewTec M13 - 8633 by Scanspeak
Impedance	8 Ω
Nominal / Music power	100 Watt / 165 Watt
Nominal sensitivity (1 W , 1 m)	82,6 dB (+ 6 dB to 360°)
Maximum SPL	104 dB (active high pass120Hz / 18 dB - Oktave)
Frequency response	110 - 20.000 Hz (+/-3 dB)
Connectors	Pole clips

CONO cubo M

Type	Wall / Ceiling mountable speaker
Principle	One way speaker
Dimensions W x L X H	110 x 110 x 105 mm
Weight	850 gr
Enclosure	carbon-fiber-reinforced plastic - Formstable up to 150° - Fireclass UL94 V-0 "self-extinguishing"
Colours	Silver, white, black- all RAL colors available on request
Equipment	1 Newtec KA10-4 by Scanspeak
Impedance	4 Ω
Nominal / Music power	50 Watt / 90 Watt
Nominal sensitivity (1 W , 1 m)	85,5 dB (+ 6 dB to 360°)
Maximum SPL	102,5 dB

Frequency response	95 - 21.000 Hz (+/-3 dB)
--------------------	--------------------------

Connectors	Pole clips
------------	------------